



Simple Solutions Distributing LLC.

Makers Of *Wolverine Brand* Activated Carbon Filters

Simple Solutions Distributing
6 Jacobs Rd.
West Milford, NJ 07480

1-866-No-Stink (1-866-667-8465-Outside NJ)
1-973-846-7817 (inside NJ and Outside of the US)
E-Mail SimpleSolution1@optonline.net

Wolverine Brand™

Activated Carbon Vent Filter: WLW-4

Installation Instructions

Your Activated carbon vent filter is shipped with the carbon in separate container.

1. Measure your vent pipe to determine its size. See the below chart to determine your nominal vent pipe size (Figure 1).
2. If your filter requires a flush bushing cement the bushing into the bottom of the filter housing. Note: Before cementing bushing into filter verify bushing fits properly on vent pipe. Flush bushings are available from any home improvement or plumbing store.
3. Place the filter housing right side up on either a rag or newspaper
4. Open the bag of carbon and pour into the fill port at the top of the filter. Occasionally shaking the filter to settle the carbon eases the filling process. Note: **Do Not** pack the carbon into the filter when the filter is full you will have about a 1/4 inch air gap between the top of the filter and the carbon.
5. Install the fill cap to the top of the filter.
6. Install filter on vent pipe. Note: **Do not** glue or cement filter to vent pipe.

Carbon Replacement.

1. Remove filter from the vent
2. Place the filter on a rag or newspaper
3. Using a small screwdriver depress the lock tab on the filler cap and remove the cap. (The lock tab located in the small slot a the top of the filter)
4. Pour the spent carbon into a suitable container and dispose of according to local, state and federal regulations.
5. Follow steps 4 thru 6 of the installation instructions.

Figure 1		
Outside Diameter (inches)	Nominal vent Pipe Size (inches)	Schedule 40 Flush Bushing required.
1.9"	1.5"	4" x 1.5"
2.375"	2"	4" x 2"
3.5"	3"	4" x 3"
4.5"	4"	No bushing required.